

APS[®]

SCS6 Cat.6 cable U/UTP 4 pairs AWG23/1, PE-ALU-PE, Fca, Direct Burial

Category 6, Unscreened pairs, 4 pairs, PE-ALU-PE Fca, underground cable

W5UX042DELEB50 , Rev.01, Date 2021-02-19

W5UX042DELEB50 , Rev.00, Date 2020-12-17



Standards of reference and applications

Outdoor LAN horizontal cabling (max 90m)

IEEE 802.3: Ethernet 10Base-T, Fast Ethernet 100Base-T, Gigabit Ethernet 1000Base-T

IEEE 802.5: ISDN, FDDI, ATM, Cable sharing

IEEE 802.3at: PoE, PoE+

EN 50288-6-1, EN 50173, EN 50174-2, ISO/IEC 11801 2., IEC 61156-5, TIA/EIA 568-B-2-1

Installation Features

Store at: -0 to +50 °C

Install at: -15 to +60 °C. **Bending radius:** 8 x Diameter.

Operate at: -40 to +70 °C. **Bending radius:** 4 x Diameter.

Tractive force: 280 N (max.)

Fire load: 0,315 kWh/m

Design

Conductor: solid bare copper AWG23 (0.99 ± 0.02 mm)

Insulation: polyethylene Ø 1.00 mm

Pair: 2 insulated conductors stranded together

Assembling: no 4 pairs assembled together around a PE central cross

Core filling: dry

Inner jacket: PE material

Moisture barrier: welded aluminium tape

Outer jacket: PE material, O.D. 9.6 ± 0.3 mm (nom.)

Marking: APS - W5UX042DELEB50 - CAT.6 U/UTP 4 PR AWG 23/1 - PE-ALU-PE - Lot no. - WW/YY - xxx
m

Colour code

1. White/blue
2. White/orange
3. White/green
4. White/brown

Environmental properties and Fire Performances

CPR Class: Fca

RoHS: 2011/65/EU

Electrical characteristics

Loop resistance: 180 Ω/km (max.)

Insulation resistance: ≥ 5 GΩ x km @+20°C

Operating capacity: 50 nF/km (nom.)

Characteristic Impedance: 100 ± 5 Ω @100MHz

Test voltage: 700V / AC

Velocity of propagation (NVP): 0.67c

Signal Term: 510 ns/100m (max.)

Running time difference: < 20 ns/100m

Coupling attenuation: > 45 dB, Type 3

Separating class: B

Frequency (MHz) :	1	4	10	16	20	31.25	62.5	100	155	200	300	350
Attenuation (dB/100m)	1,8	3,5	5,6	7,0	7,9	10,4	13,8	18,2	22,5	26,0	32,5	35,2
NEXT (dB)	87	76	72	70	68	66	65	63	60	57	55	54
PSANEXT (dB)	85	72	66	63	60	56	51	45	37	61	23	19
ACR (dB/100m)	85	72	63	60	58	54	51	43	40	38	36	34
ELFEXT (dB/100m)	25	28	30	30	30	30	30	30	30	29	28	27
RL (dB)	20.0	23.0	24.5	25.0	25.0	25.0	24.3	23.6	21.5	20.1	18.0	17.3

Ordering and delivery information

Pair	P/N	O.D.	Weight	Retail	Wholesale	STK Electrical	GTIN
------	-----	------	--------	--------	-----------	-------------------	------

count		[mm]	[kg/km]	packaging	packaging	No.	
4 pairs	W5UX042DELEB50	9.6±0.3	78	500 m (drum) 60x60x45 cm 47 kg	2000 m (pallet) 120x80x100 cm 210,0 kg	02 331 15	6410002331158

Recommended connectivity

	APS		Kerman		System warranty
Keystone jack (tool type)	-	-	GT624	72 477 03	Not included
Keystone jack (tool type)	-	-	CM624	72 477 05	Not included
Keystone jack (tool type)	-	-	GT6	72 093 16	Not included
Keystone jack (toolless)	GSCAT6AU	72 058 68	CM6	72 094 39	Not included
Keystone jack (toolless)	GSCAT6AU24	72 058 77	-	-	Not included
Patch panel	PPE24SU	72 265 11	KRM24H	72 094 07	Not included
Field connector RJ45 (toolless)	-	-	KRJ45U-U	72 477 00	Not included
Connection box (tool type)	-	-	KRM6KJ	72 473 16	Not included

Every effort has been put so that this document is most reliable and free from errors. However, AP Solutions Oy cannot be considered responsible for any mistake in this document and users should consult AP Solutions Oy for any information needed. AP Solutions Oy reserves the right to make changes to the documents at any time, without prior notice.